

# Hand lever valve
# VHER-H-B43C-B-N14

Part number: 3520389






## Data sheet

| Feature | Value |
|---|---|
| Valve function | 4/3-way, closed |
| Actuation type | Manual |
| Width | 56 mm |
| Normal nominal flow rate (normalized to DIN 1343) | 1500 l/min |
| Pneumatic working port | NPT1/4-18 |
| Operating pressure | 0 bar...10 bar |
| Information on operating pressure | Vacuum operation at connection 3 only<br>In dual pressure mode, the pressure at port 1 must be higher than at port 3. |
| Structural design | Rotary vane |
| Nominal width | 8 mm |
| Exhaust air function | Adjustable |
| Application note | Only operate by hand |
| Sealing principle | Hard |
| Type of control | directly |
| Flow direction | Non-reversible |
| Underlap | Yes |
| Switching position indication | with accessories |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Temperature of medium | -20 °C...80 °C |
| Ambient temperature | -20 °C...80 °C |
| Actuating torque | 2 Nm |
| Product weight | 510 g |
| Type of mounting | Alternatively:<br>Front panel mounting<br>With through-hole |
| Pneumatic connection 1 | NPT1/4-18 |
| Pneumatic connection 2 | NPT1/4-18 |
| Pneumatic connection 3 | NPT1/4-18 |

| Feature | Value |
|---|---|
| Pneumatic connection 4 | NPT1/4-18 |
| Note on materials | RoHS compliant |
| Seals material | NBR |
| Housing material | Die-cast aluminum |
| Lever material | Die-cast aluminum |