
# Air solenoid valve
# MHE3-MS1H-3/2G-QS-6

Part number: 525151






## Data sheet

| Feature | Value |
|---|---|
| Valve function | 3/2-way, closed, monostable |
| Actuation type | Electrical |
| Width | 14 mm |
| Normal nominal flow rate (normalized to DIN 1343) | 200 l/min |
| Pneumatic working port | QS-6 |
| Operating voltage | 24V DC |
| Operating pressure | -0.09 MPa...0.8 MPa<br>-0.9 bar...8 bar<br>-13.05 psi...116 psi |
| Structural design | Pressure relief poppet valve |
| Reset method | Mechanical spring |
| Degree of protection | IP65 |
| Certification | RCM compliance mark<br>c UL us - recognized (OL) |
| CE marking (see declaration of conformity) | As per EU EMC directive<br>As per EU RoHS directive |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC<br>To UK RoHS instructions |
| Nominal width | 3 mm |
| Width dimension | 19 mm |
| Note on grid dimension | Minimum distance between the valves is 5 mm |
| Exhaust air function | Adjustable |
| Sealing principle | Soft |
| Mounting position | Any |
| Manual override | Non-detenting |
| Type of control | directly |
| Flow direction | Reversible with restrictions |
| Lap | Negative overlap |
| Reverse polarity protection | Bipolar |
| Additional functions | Spark arresting<br>Holding current reduction<br>Protective circuit |
| Operating pressure, reversible | -0.09 MPa...0.1 MPa<br>-0.9 bar...1 bar |

| Feature | Value |
|---|---|
| | -13.05 psi...14.5 psi |
| Max. switching frequency | 280 Hz |
| Switching time off | 2.8 ms |
| On switching time | 2.3 ms |
| Tolerance for switching time off | +10%/-50% |
| Tolerance for ON switching time | +10%/-30% |
| Switching time variation at 1 Hz and above | 0.2 ms |
| Duty cycle | 100% |
| Coil characteristics | 24 V DC: low-current phase 1.6 W, high-current phase 6.5 W |
| Permissible voltage fluctuations | +/- 10% |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Vibration resistance | Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6 |
| Restricted ambient and media temperature | Depending on the switching frequency (see diagram) |
| Shock resistance | Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27 |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 6 according to ISO 14644-1 |
| Temperature of medium | -5 °C...60 °C |
| Ambient temperature | -5 °C...60 °C |
| Product weight | 120 g |
| Electrical connection | 2-pin<br>Plug |
| Type of mounting | With through-hole |
| Pneumatic connection 1 | QS-6 |
| Pneumatic connection 2 | QS-6 |
| Pneumatic connection 3 | QS-6 |
| Note on materials | RoHS compliant |
| Seals material | HNBR<br>NBR |
| Housing material | Die-cast zinc, coated |
| Material of screws | Galvanized steel |