# Multiple distributor
# QST3-8-6

Part number: 153204



## Data sheet

| Feature | Value |
|---|---|
| Size | Standard |
| Nominal width | 3.6 mm |
| Tubing insertion depth | 17 mm<br>18 mm |
| Note on the tubing insertion depth | Ø6 depth 17 mm<br>Ø8 depth 18 mm |
| Mounting position | Any |
| Structural design | Push-pull principle |
| Pack size | 1 |
| Operating pressure for entire temperature range | -0.095 MPa...0.6 MPa<br>-0.95 bar...6 bar<br>-13.775 psi...87 psi |
| Temperature-dependent operating pressure | -0.095 MPa...1.4 MPa<br>-0.95 bar...14 bar<br>-13.775 psi...203 psi |
| Information on operating pressure | Water: max. 0.6 MPa at 0 - 50 °C |
| Maritime classification | See certificate |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:-:-]<br>Water (liquid, ice-free) |
| Information on operating and pilot media | Lubricated operation possible |
| Corrosion resistance class (CRC) | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Ambient temperature | -10 °C...80 °C |
| Product weight | 23 g |
| No. of outlets | 4 |
| No. of supply lines | 1 |
| Pneumatic connection 1 | for pneumatic tubing outside diameter 8 mm |
| Pneumatic connection 2 | for pneumatic tubing outside diameter 6 mm |
| Releasing ring color | Blue |
| Note on materials | RoHS compliant |
| Housing material | PBT |
| Releasing ring material | POM |
| Material of tubing seal | NBR |

| Feature | Value |
|---|---|
| Material of tube retaining claw | high-alloy stainless steel |