
# Service unit
# FRCS-1/2-D-MIDI-A

Part number: 194913






## Data sheet

| Feature | Value |
|---|---|
| Size | Midi |
| Series | D |
| Actuator lock | Rotary knob with integrated lock |
| Mounting position | Vertical ±5° |
| Condensate drain | Fully automatic |
| Structural design | Filter regulator with pressure gauge<br>Proportional standard oil mist lubricator |
| Max. condensate volume | 43 cm³ |
| Grade of filtration | 40 µm |
| Bowl guard | Metal bowl guard |
| Pressure gauge | with pressure gauge |
| Operating pressure | 0.2 MPa...1.2 MPa<br>2 bar...12 bar |
| Pressure regulation range | 0.5 bar...12 bar |
| Max. pressure hysteresis | 0.02 MPa<br>0.2 bar<br>2.9 psi |
| Normal nominal flow rate (normalized to DIN 1343) | 2600 l/min |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:9:-]<br>Inert gases |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Air quality class at the output | Compressed air as per ISO 8573-1:2010 [7:8:-]<br>Inert gases |
| Temperature of medium | -10 °C...60 °C |
| Ambient temperature | -10 °C...60 °C |
| Product weight | 1680 g |
| Type of mounting | In-line installation<br>With accessories |
| Pneumatic connection 1 | G1/2 |
| Pneumatic connection 2 | G1/2 |
| Note on materials | RoHS compliant |
| Housing material | Die-cast zinc |

| Feature | Value |
|---|---|
| Material of bowl | PC |