
# Vertical pressure shut-off plate
# VABF-S2-1-L1D1-C

Part number: 546096






## Data sheet

| Feature | Value |
|---|---|
| Width | 43 mm |
| Based on norm | ISO 5599-2 |
| Mounting position | Any |
| Pneumatic vertical stacking | Shut-off for 1 |
| Operating pressure | -0.09 MPa...1 MPa<br>-0.9 bar...10 bar |
| Normal nominal flow rate (normalized to DIN 1343) | 1200 l/min |
| CE marking (see declaration of conformity) | as per EU simple pressure vessel directive |
| UKCA marking (see declaration of conformity) | To UK instructions for electrical equipment |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 0 - No corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Degree of protection | IP65<br>NEMA 4 |
| Ambient temperature | -5 °C...50 °C |
| Product weight | 600 g |
| Vertical stacking mounting type | On manifold sub-base<br>On individual sub-base |
| Note on materials | RoHS compliant |
| Housing material | Die-cast aluminum |