# Plug socket
# MSSD-V

Part number: 33295



## Data sheet

| Feature | Value |
|---|---|
| Type of mounting | On air solenoid valve with M3 central screw |
| Cable outlet | Angled |
| Note on cable outlet | Can be rotated through 180° |
| Mounting position | Any |
| Product weight | 18 g |
| Electrical connection | 3-pin<br>Socket<br>Angled socket<br>Form B<br>As per DIN EN 175301-803<br>Rectangular design MSV |
| Electrical connection 1, design | Square |
| Electrical connection 1, connection type | Socket |
| Electrical connection 1, cable outlet | Angled |
| Electrical connection 1, number of pins/wires | 3 |
| Electrical connection 2 | Screw terminal |
| DC operating voltage range | 0 V...250 V |
| Operating voltage range AC | 0 V...250 V |
| Current rating at 40° C | 16 A |
| Protective earth connection | Available |
| Cable fitting | Pg9 |
| Cable diameter | 6 mm...8 mm |
| Nominal conductor cross section | 1.5 mm² |
| Degree of protection | IP65 |
| Note on degree of protection | In mounted state |
| Ambient temperature | -25 °C...90 °C |
| CE marking (see declaration of conformity) | As per EU low voltage directive<br>As per EU RoHS directive |
| UKCA marking (see declaration of conformity) | To UK RoHS instructions<br>To UK instructions for electrical equipment |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Housing material | Polymer |
| Housing colour | Black |

| Feature | Value |
| --- | --- |
| Seals material | NBR |