
# Air preparation combination unit
# MSB6N-3/8-FRC11:J9M2

Part number: 534031






## Data sheet

| Feature | Value |
|---|---|
| Size | 6 |
| Series | MS |
| Actuator lock | Rotary knob with integrated lock |
| Mounting position | Vertical ±5° |
| Grade of filtration | 5 µm |
| Condensate drain | Manual, rotating |
| Structural design | Filter regulator with pressure gauge<br>Proportional standard oil mist lubricator |
| Controller function | Constant output pressure<br>With primary pressure compensation<br>With secondary exhausting<br>With return flow characteristic |
| Bowl guard | Integrated as metal bowl |
| Pressure gauge | with pressure gauge |
| Operating pressure | 1.5 bar...20 bar |
| Pressure regulation range | 0.5 bar...12 bar |
| Normal nominal flow rate (normalized to DIN 1343) | 3400 l/min |
| Operating medium | Compressed air as per ISO 8573-1:2010 [-:4:-]<br>Inert gases |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Storage temperature | -10 °C...60 °C |
| For use in the food industry | See supplementary material information |
| Air quality class at the output | Compressed air as per ISO 8573-1:2010 [6:4:-] |
| Temperature of medium | -10 °C...60 °C |
| Ambient temperature | -10 °C...60 °C |
| Product weight | 1713 g |
| Type of mounting | With accessories |
| Pneumatic connection 1 | 3/8 NPT |
| Pneumatic connection 2 | 3/8 NPT |
| Note on materials | RoHS compliant |