
# Connecting cable
# KMYZ-2-24-2,5-LED

Part number: 34997



## Data sheet

| Feature | Value |
|---|---|
| Maritime classification | See certificate |
| Switching position indication | LED |
| Type of mounting | On air solenoid valve with self-tapping screw |
| Mounting position | Any |
| Product weight | 50 g |
| Electrical connection | 2-pin/2-core<br>Angled socket/cable<br>Rectangular design/open end |
| Nominal operating voltage DC | 24 V |
| Current rating at 40° C | 1 A |
| Protective earth connection | Not available |
| Cable length | 2.5 m |
| Cable characteristic | Standard |
| Cable diameter | 3.4 mm |
| Cable design | 2 x 0.25 mm² |
| Degree of protection | IP65 |
| Ambient temperature | -10 °C...50 °C |
| CE marking (see declaration of conformity) | As per EU RoHS directive |
| UKCA marking (see declaration of conformity) | To UK RoHS instructions |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Note on materials | RoHS compliant |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| Material of cable sheath | TPE-U(PUR) |
| Housing material | PA |
| Material of pin contacts | Bronze |