

# Pneumatic valve
# VL-5-PK-3

Part number: 4504






## Data sheet

| Feature | Value |
|---|---|
| Valve function | 5/2-way, monostable |
| Normal nominal flow rate (normalized to DIN 1343) | 105 l/min |
| Pneumatic working port | PK-3 |
| Operating pressure | 1.5 bar...8 bar |
| Structural design | Plate seat |
| Nominal width | 2.5 mm |
| Switching time off | 22 ms |
| On switching time | 15 ms |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:-:-] |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Ambient temperature | -10 °C...60 °C |
| Product weight | 130 g |
| Type of mounting | Alternatively:<br>On sub-base<br>On mounting frame<br>With through-hole |
| Pneumatic connection 1 | PK-3 |
| Pneumatic connection 2 | PK-3 |
| Pneumatic connection 3 | PK-3 |
| Pneumatic connection 4 | PK-3 |
| Pneumatic connection 5 | PK-3 |
| Note on materials | RoHS compliant |
| Material of sub-base | Brass<br>PPS-reinforced |
| Seals material | NBR |
| Housing material | Polymer<br>Die-cast zinc |