
# Pressure sensor
# SPAN-B2R-G18M-PN-PN-L1

Part number: 8035545






## Data sheet

| Feature | Value |
|---|---|
| Certification | RCM compliance mark<br>c UL us - Listed (OL) |
| CE marking (see declaration of conformity) | As per EU EMC directive<br>As per EU RoHS directive |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC<br>To UK RoHS instructions |
| Certificate issuing authority | UL E322346 |
| Note on materials | RoHS compliant |
| Measured variable | Relative pressure |
| Method of measurement | Piezoresistive pressure sensor |
| Pressure measuring range initial value | -0.1 MPa<br>-1 bar<br>-14.5 psi |
| Pressure measuring range end value | 0.1 MPa<br>1 bar<br>14.5 psi |
| Max. overload pressure | 5 bar |
| Overload pressure | 0.5 MPa<br>5 bar<br>72.5 psi |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4]<br>Inert gases |
| Information on operating and pilot media | Lubricated operation possible |
| Temperature of medium | 0 °C...50 °C |
| Ambient temperature | 0 °C...50 °C |
| Accuracy in ± % FS | 1.5 %FS |
| Repetition accuracy in ± %FS | 0.3 %FS |
| Temperature co-efficient in ± %FS/K | 0.05 %FS/K |
| Switching output | 2 x PNP or 2 x NPN switchable |
| Switching function | Window comparator<br>Threshold value comparator<br>Auto difference monitoring |
| Switching element function | N/C contact/N/O contact, switchable |
| Max. output current | 100 mA |
| Short-circuit protection | Yes |

| Feature | Value |
|---|---|
| DC operating voltage range | 15 V...30 V |
| Reverse polarity protection | for all electrical connections |
| Electrical connection 1, connection type | Plug |
| Electrical connection 1, connection technology | Connection pattern L1J |
| Electrical connection 1, number of pins/wires | 4 |
| Type of mounting | Front panel mounting<br>With thread<br>With wall/surface bracket |
| Mounting position | Any |
| Pneumatic connection | External thread G1/8<br>Internal thread M5 |
| Product weight | 46 g |
| Housing material | PA-reinforced |
| Materials in contact with the media | FPM<br>high-alloy stainless steel |
| Display type | Illuminated LCD |
| Displayable unit(s) | MPa<br>bar<br>In H2O<br>In Hg<br>KPa<br>kgf/cm²<br>mbar<br>mmHg<br>psi |
| Setting options | Teach-in<br>Via display and keys |
| Protection against tampering | PIN code |
| Setting range threshold value | 0 %...100 % |
| Setting range hysteresis | 0 %...90 % |
| Degree of protection | IP40 |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Suitability for the production of Li-ion batteries | Suitable for battery production with reduced Cu/Zn/Ni values (F1a) |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 4 according to ISO 14644-1 |