
# Proximity sensor
# SIEN-M5B-PO-K-L

Part number: 150374






## Data sheet

| Feature | Value |
|---|---|
| Conforms to standard | EN 60947-5-2 |
| Certification | RCM compliance mark<br>c UL us - Listed (OL) |
| CE marking (see declaration of conformity) | As per EU EMC directive<br>As per EU RoHS directive |
| UKCA marking (see declaration of conformity) | according to UK regulations for EMC (UK-E)<br>according to UK RoHS regulations (UK-R) |
| Note on materials | RoHS compliant |
| Rated operating distance | 0.8 mm |
| Ambient temperature | -25 °C...70 °C |
| Repetition accuracy under constant conditions | 0.01 mm |
| Switching output | PNP |
| Switching element function | NC contact |
| Max. switching frequency | 5000 Hz |
| Max. output current | 200 mA |
| Short-circuit protection | Pulsed |
| DC operating voltage range | 10 V...30 V |
| Reverse polarity protection | for all electrical connections |
| Electrical connection 1, connection type | Cable |
| Electrical connection 1, connection technology | Open end |
| Electrical connection 1, number of pins/wires | 3 |
| Cable length | 2.5 m |
| Material of cable sheath | TPE-U(PUR) |
| Size | M5x0.5 |
| Type of mounting | With locknut |
| Tightening torque | 1.5 Nm |
| Mounting type | Flush |
| Product weight | 33.6 g |
| Housing material | PA<br>high-alloy stainless steel |
| Switching status indication | Yellow LED |
| Ambient temperature with flexible cable installation | -5 °C...70 °C |

| Feature | Value |
|---|---|
| Degree of protection | IP67 |
| Surge resistance | 1 kV |
| Corrosion resistance class (CRC) | 4 - Particularly high corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Contamination level | 3 |
| Selection of additional sensor information | With standard switching distance |
| Electrical output | PNP |
| Selection of sensor version | Standard |