

# Air solenoid valve
# VMPA14-M1H-K-PI

Part number: 573724






## Data sheet

| Feature | Value |
|---|---|
| Valve function | 2x3/2 closed, monostable |
| Actuation type | Electrical |
| Valve size | 14 mm |
| Normal nominal flow rate (normalized to DIN 1343) | 550 l/min...600 l/min |
| Operating voltage | 24V DC |
| Operating pressure | 0.3 MPa...1 MPa<br>3 bar...10 bar |
| Structural design | Piston gate valve |
| Reset method | Pneumatic spring |
| Certification | c UL us - recognized (OL) |
| Degree of protection | IP65<br>In mounted state<br>As per IEC 60529 |
| Sealing principle | Soft |
| Mounting position | Any |
| Manual override | Detenting<br>Non-detenting |
| Type of control | Piloted |
| Flow direction | Non-reversible |
| Lap | Positive overlap |
| Signal status display | Yes |
| Pilot pressure MPa | 0.3 MPa...0.8 MPa |
| Pilot pressure | 3 bar...8 bar |
| Suitability for vacuum | No |
| Note on standard nominal flow rate | MPA-L: 600 l/min<br>MPA-S: 550 l/min |
| Standard nominal flow rate with QS-8 | 550 l/min...600 l/min |
| Switching time off | 28 ms |
| On switching time | 10 ms |
| Max. positive test pulse with 0 signal | 400 µs |
| Max. negative test pulse on 1 signal | 200 µs |
| Permissible voltage fluctuations | +/- 25% |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |

| Feature | Value |
|---|---|
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Vibration resistance | Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6 |
| Shock resistance | Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27 |
| Corrosion resistance class (CRC) | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Storage temperature | -20 °C...40 °C |
| Temperature of medium | -5 °C...50 °C |
| Relative air humidity | Max. 90% at 40°C |
| Ambient temperature | -5 °C...50 °C |
| Max. tightening torque for valve mounting | 0.65 Nm |
| Product weight | 77 g |
| Type of mounting | With through-hole |
| Note on materials | RoHS compliant |
| Seals material | NBR |
| Housing material | Die-cast aluminum |