


# One-way flow control valve GGO-1/4-3/8

Part number: 3634

**FESTO**



## Data sheet

| Feature                                              | Value                                                              |
|------------------------------------------------------|--------------------------------------------------------------------|
| Valve function                                       | One-way flow control function                                      |
| Pneumatic connection 1                               | G1/4                                                               |
| Pneumatic connection 2                               | G1/4                                                               |
| Actuation type                                       | Mechanical                                                         |
| Adjusting element                                    | Roller lever                                                       |
| Type of mounting                                     | With through-hole                                                  |
| Standard nominal flow rate in flow control direction | 950 l/min                                                          |
| Standard nominal flow rate in non-return direction   | 1150 l/min                                                         |
| Operating pressure                                   | 0.03 bar...8 bar<br>0.43 psi...116 psi                             |
| Ambient temperature                                  | -10 °C...60 °C                                                     |
| Housing material                                     | Wrought aluminum alloy                                             |
| Mounting position                                    | Any                                                                |
| Operating medium                                     | Compressed air as per ISO 8573-1:2010 [7:-:-]                      |
| Information on operating and pilot media             | Operation with oil lubrication possible (required for further use) |
| LABS (PWIS) conformity                               | VDMA24364-B2-L                                                     |
| Temperature of medium                                | -10 °C...60 °C                                                     |
| Product weight                                       | 400 g                                                              |
| Seals material                                       | NBR                                                                |