

# Solenoid valve
# VUVG-B18-P53C-Z-F-P1

Part number: 8033568






## Data sheet

| Feature | Value |
|---|---|
| Valve function | 5/3-way, closed |
| Actuation type | Electrical |
| Valve size | 18 mm |
| Normal nominal flow rate (normalized to DIN 1343) | 950 l/min |
| Pneumatic working port | Flange |
| Operating pressure | -0.09 MPa...1 MPa<br>-0.9 bar...10 bar |
| Structural design | Piston gate valve |
| Reset method | Mechanical spring |
| Certification | c UL us - recognized (OL) |
| CE marking (see declaration of conformity) | As per EU EMC directive<br>As per EU low voltage directive<br>As per EU RoHS directive |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC<br>To UK RoHS instructions<br>To UK instructions for electrical equipment |
| Certificate issuing authority | UL MH19482 |
| Degree of protection | IP65<br>With electrical pilot valve and plug socket |
| Nominal width | 6.5 mm |
| Exhaust air function | Adjustable |
| Sealing principle | Soft |
| Mounting position | Any |
| Type of control | Piloted |
| Pilot air supply port | External |
| Lap | Positive overlap |
| Pilot pressure MPa | 0.3 MPa...0.8 MPa |
| Pilot pressure | 3 bar...8 bar |
| Switching time off | 32 ms |
| On switching time | 15 ms |
| Changeover time | 21 ms |
| Duty cycle | 100% |
| Max. positive test pulse with 0 signal | 700 µs |

| Feature | Value |
|---|---|
| Max. negative test pulse on 1 signal | 900 µs |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Vibration resistance | Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6 |
| Shock resistance | Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27 |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 5 according to ISO 14644-1 |
| Temperature of medium | -5 °C...60 °C |
| Ambient temperature | -5 °C...60 °C |
| Product weight | 136 g |
| Electrical connection | Via electric pilot valve |
| Type of mounting | On terminal strip |
| Pilot interface | As per ISO 15218 |
| Note on materials | RoHS compliant |
| Seals material | HNBR<br>NBR |
| Housing material | Wrought aluminum alloy |