

# Compact cylinder
# DPDM-Q-25-15-PA

Part number: 4840826





## Data sheet

| Feature | Value |
|---|---|
| Stroke | 15 mm |
| Piston diameter | 25 mm |
| Cushioning | Elastic cushioning rings/pads at both ends |
| Mounting position | Any |
| Mode of operation | Double-acting |
| Structural design | Piston<br>Piston rod<br>Profile barrel |
| Position sensing | Via proximity switch |
| Variants | Piston rod at one end |
| Protection against torsion/guide | Guide rod with yoke |
| Operating pressure | 0.1 MPa...0.8 MPa<br>1 bar...8 bar |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 6 according to ISO 14644-1 |
| Ambient temperature | -10 °C...80 °C |
| Theoretical force at 6 bar | 295 N |
| Theoretical force at 6 bar, retracting | 247 N |
| Theoretical force at 6 bar, advancing | 295 N |
| Moving mass at 0 mm stroke | 76 g |
| Additional moving mass per 10 mm stroke | 8 g |
| Basic weight with 0 mm stroke | 223 g |
| Additional weight per 10 mm stroke | 35 g |
| Type of mounting | Alternatively:<br>With through-hole<br>With internal thread |
| Pneumatic connection | M5 |
| Note on materials | RoHS compliant |
| Cover material | Wrought aluminum alloy |
| Seals material | TPE-U(PU) |

| Feature | Value |
|---|---|
| Housing material | Wrought aluminum alloy, anodized |
| Piston rod material | high-alloy stainless steel |