

# Air solenoid valve
# VSVA-B-B52-H-A2-1R2L

Part number: 534776






## Data sheet

| Feature | Value |
|---|---|
| Valve function | 5/2-way, bistable |
| Actuation type | Electrical |
| Width | 18 mm |
| Normal nominal flow rate (normalized to DIN 1343) | 550 l/min |
| Pneumatic working port | Sub-base, size 18 mm as per ISO 15407-1<br>Connecting plate size 02 according to VDMA 24563 |
| Operating voltage | 24V DC |
| Operating pressure | 0.3 MPa...0.8 MPa<br>3 bar...8 bar |
| Structural design | Piston gate valve |
| Certification | C-Tick<br>c UL us - recognized (OL) |
| CE marking (see declaration of conformity) | As per EU EMC directive |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC<br>To UK RoHS instructions |
| Degree of protection | IP65 |
| Nominal width | 5 mm |
| Exhaust air function | Adjustable |
| Sealing principle | Soft |
| Mounting position | Any |
| Conforms to standard | ISO 15407-1<br>VDMA 24563 |
| Manual override | Non-detenting |
| Type of control | Piloted |
| Pilot air supply port | Internal |
| Flow direction | Non-reversible |
| Lap | Positive overlap |
| Reverse polarity protection | for all electrical connections |
| Additional functions | Holding current reduction<br>Safety shut-off |
| Signal status display | LED |
| Flow rate of pneumatic valve | 750 l/min |
| Flow rate of pneumatic valve on individual sub-base | 550 l/min |

| Feature | Value |
|---|---|
| Optimized flow rate of pneumatic valve pneumatically concatenated flow | 550 l/min |
| Changeover time | 10 ms |
| DC operating voltage range | 21.6 V...26.4 V |
| Duty cycle | 100% |
| Max. positive test pulse with 0 signal | 500 µs |
| Max. negative test pulse on 1 signal | 500 µs |
| Coil characteristics | 24 V DC: low-current phase 1.0 W, high-current phase 2.4 W |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Vibration resistance | Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6 |
| Shock resistance | Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27 |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Temperature of medium | -5 °C...50 °C |
| Relative air humidity | 0 - 90% |
| Protection against direct and indirect contact | PELV |
| Ambient temperature | -5 °C...50 °C |
| Max. tightening torque for valve mounting | 0.9 Nm...1.1 Nm |
| Product weight | 140 g |
| Electrical connection | 4-pin<br>M8x1<br>Central plug<br>Round design |
| Type of mounting | On sub-base |
| Note on materials | RoHS compliant |