
# Fine filter
# MS6N-LFM-1/2-BRM-DA

Part number: 536853






## Data sheet

| Feature | Value |
|---|---|
| Series | MS |
| Size | 6 |
| Structural design | Fiber filter |
| Grade of filtration | 1 µm |
| Condensate drain | Manual, rotating |
| Operating pressure | 0 MPa...2 MPa<br>0 bar...20 bar<br>0 psi...290 psi |
| Operating medium | Compressed air as per ISO 8573-1:2010 [6:4:4]<br>Inert gases |
| Air quality class at the output | Compressed air according to ISO 8573-1:2010 [5:4:3] |
| Max. standard flow rate for air quality class | 950 l/min |
| Min. standard flow rate for air quality class | 140 l/min |
| Filter efficiency | 99.99 % |
| Max. condensate volume | 38 cm³ |
| Bowl guard | Plastic bowl guard |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| For use in the food industry | See supplementary material information |
| Temperature of medium | -10 °C...60 °C |
| Ambient temperature | -10 °C...60 °C |
| Storage temperature | -10 °C...60 °C |
| Filter efficiency, fine particles | 99 % |
| Residual oil content | 0.5 mg/m³ |
| Filter efficiency, oil aerosol | 90 % |
| Differential pressure display | Visual display |
| Type of mounting | Alternatively:<br>In-line installation<br>With accessories |
| Mounting position | Vertical ±5° |

| Feature | Value |
|---|---|
| Pneumatic connection 1 | 1/2 NPT |
| Pneumatic connection 2 | 1/2 NPT |
| Housing material | Die-cast aluminum |
| Compressed air filter material | Borosilicate glass fiber |
| Material of bowl | PC |
| Seals material | NBR |
| Note on materials | RoHS compliant |
| Product weight | 600 g |