
# Three-point gripper
# HGDT-40-A-G1

Part number: 540866





## Data sheet

| Feature | Value |
|---|---|
| Size | 40 |
| Stroke per gripper jaw | 6 mm |
| Max. interchangeability | 0.2 mm |
| Max. gripper jaw angular play ax, ay | 0.1 deg |
| Max. gripper jaw backlash Sz | 0.05 mm |
| Rotational symmetry | 0.2 mm |
| Pneumatic gripper repetition accuracy | 0.03 mm |
| Number of gripper jaws | 3 |
| Mounting position | Any |
| Mode of operation | Double-acting |
| Gripper function | 3-point |
| Gripping force backup | On opening |
| Structural design | Inclined plane<br>Positively driven motion sequence |
| Position sensing | Via proximity switch |
| Operating pressure | 4 bar...8 bar |
| Operating pressure for sealing air | 0 bar...0.5 bar |
| Max. operating frequency of pneumatic gripper | 4 Hz |
| Min. opening time at 6 bar | 58 ms |
| Min. closing time at 6 bar | 160 ms |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Ambient temperature | 5 °C...60 °C |
| Mass moment of inertia | 5.59 kgcm² |
| Maximum force on gripper jaw Fz, static | 800 N |
| Maximum torque on gripper jaw, Mx static | 30 Nm |
| Maximum torque on gripper jaw, My static | 20 Nm |
| Maximum torque on gripper jaw, Mz static | 25 Nm |
| Relubrication interval for guidance elements | 5 MioCyc |
| Max. mass per external gripper finger | 70 g |

| Feature | Value |
|---|---|
| Product weight | 840 g |
| Type of mounting | Alternatively:<br>With through-hole and dowel pin<br>With internal thread and dowel pin |
| Sealing air pneumatic connection | M5 |
| Pneumatic connection | M5 |
| Cover cap material | high-alloy stainless steel |
| Housing material | Wrought aluminum alloy<br>COMPCOTE-coated |
| Gripper jaw material | Hardened steel |