
# Electrical interface
# VMPA-ASI-EPL-EU-8E8A-Z

Part number: 546994



## Data sheet

| Feature | Value |
|---|---|
| Dimensions W x L x H | 85 mm x 122.9 mm x 55.1 mm |
| Fieldbus interface | Socket, M12 (AS-i Out)<br>Plug, M12 (AS-i In) |
| Device-specific diagnostics | AS-i voltage<br>AS-i address<br>Watchdog/I/O status<br>Additional supply missing or undervoltage |
| Max. no. of valve positions | 8 |
| Response delay inputs | Typ. 3 ms at 24 V |
| Number of slaves per device | 2 |
| Operating voltage range DC electronics/sensors | US+ / US- : <= AS-interface bus voltage - 2.5V |
| AS-Interface DC operating voltage range | 26.5 V...31.6 V |
| DC load voltage operating voltage range | 21.6 V...26.4 V |
| Information concerning load voltage | Via load voltage connection (24 V DC) |
| Logic level digital inputs | ON: 11 - 30V<br>OFF: -30 - 5V |
| Max. number of inputs | 8 |
| AS interface residual ripple | <= 20 mVss |
| Load voltage residual ripple | 4 Vss |
| Current consumption with load voltage from AS-Interface and load voltage connection | Max. total current at inputs 350 mA<br>Max. total current at outputs MPA1: 540 mA<br>Max. total current at outputs MPA2: 1065 mA |
| Corrosion resistance class (CRC) | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Storage temperature | -20 °C...40 °C |
| Degree of protection | IP20 |
| Ambient temperature | -5 °C...50 °C |
| Product weight | 360 g |
| Input characteristics | As per IEC 1131-2, type 02 |
| Input switching logic | PNP (positive switching) |
| Addressing range | Standard slave: 1 ... 31 |
| LED display (bus-specific) | AS-i: AS-Interface operation<br>Aux/Pwr: AS-Interface power supply<br>Error: AS-Interface error |

| Feature | Value |
|---|---|
| LED display (product-specific) | Signal at input/output |
| Product identification | ID code: ID code: ID=Fh, ID1=Fh, ID2=Eh<br>IO code: 7h<br>Profile: S-7.F.E |
| Type of mounting | Alternatively:<br>With through-hole<br>With DIN rail |
| Housing material | Die-cast aluminum<br>PA |
| Note on materials | RoHS compliant |